


Diaphragm Pump for housing mounting.

To the promotion of gaseous media at technology (A-1)





Made in Germany – ISO 9001 certified


more information: PB-30
www.hyco.de



Technology (A-1)



Technical Data:		ML65-W14	ML75-W14	ML86-W14
Free flow (at 20°C)	l/min	8,5	23,5	33
Final vacuum	mbar	150	100	100
Final pressure	(abs.)	4 bar	3 bar	2 bar
Pump heads		1		
Hose coupling, suction / pressure		G 1/4"		
Mains requirement - Frequencies		230V-50Hz or 230/400V-50Hz		
Motor power / r.p.m.		0,15 - 0,18 KW / 1400 min ⁻¹		
Ex-Motor		upon request		
DC Motor		upon request		
Noise level	dB(A)	49 to 53		
Permissible gas admission temp.	°C	+ 100		
Permissible ambient temperature		+ 100		
Permissible ambient temperature		+ 5 to + 45		
Motor °C				
Dimensions mm	L x W x H	386 x 120 x 182,5		
Weight ca.	kg	10,0		
Impermeable to gas		1 x 10 ⁻³ mbar x l/s (unexamined)		



hyco Vakuumtechnik GmbH

Konrad-Zuse-Bogen 1 • D-82152 Krailing (Germany) • Tel.: +49 (0)89-85661900 • Fax: +49 (0)89-85661901
 Internet: www.hyco.de • eMail: info@hyco.de