

8-Cylinder Diaphragm Pump


To the promotion of gaseous media at technology (A-1)

Made in Germany – ISO 9001 certified




hyco®

more information: PB-25


www.hyco.de



Technology (A-1)



Technical Data:	MML75.85	MML75.86	MML75.88	MML86.85	MML86.86	MML86.88
Free flow l/min	155	97	77,5	230	132	114
Final vacuum mbar	90	12	2	80	15	3
Final pressure (abs.)	2 bar			1 bar		
Pump heads	8					
Hose coupling, suction / pressure	G1/2" or G1/4"					
Mains requirement - Frequencies	230V-50Hz or 230/400V-50Hz					
Motor power / r.p.m.	0,45 - 0,75 KW / 1400 min ⁻¹					
Ex-Motor	upon request					
Noise level dB(A)	58 to 60					
Permissible gas admission temp. °C	+ 5 to + 45					
Permissible ambient temperature °C	+ 5 to + 45					
Dimensions mm L x W x H	440 x 243 x 243					
Weight ca. kg	24,5					
Impermeable to gas	1 x 10 ⁻³ mbar x l/s (unexamined)					



hyco Vakuumtechnik GmbH

Konrad-Zuse-Bogen 1 • D-82152 Krailing (Germany) • Tel.: +49 (0)89-85661900 • Fax: +49 (0)89-85661901

Internet: www.hyco.de • eMail: info@hyco.de